

Product sheet

Surge Protector 3P Type 1+2 25 kA

Brand: SCHNEIDER

Reference: IMPO 16331



Surge protector type 1+2 with plug-in cartridge for 3P electrical distribution networks, 230/400 V AC, 50/60 Hz. Uses MOV technology with inter-electrode distance, response ≤ 25 ns, and protection level < 1.5 kV in common mode. Supports nominal discharge current 25 kA (L/PE), maximum operating voltage 350 V L/PE, and short-circuit withstand capability of 25 kA. Mounting on DIN rail, IP40 (frontal) protection rating, CE certified according to EN 61643-11:2012.

[View product online](#)

Description

Surge protector type 1+2 with plug-in cartridge for 230/400 V AC, 3-pole electrical distribution networks, designed to protect installations in small commercial environments. Utilizes MOV technology with inter-electrode distance and provides response time up to 25 ns.

Specifications

Frequency	50/60 Hz
High	90 mm
Rated current (A)	25
Width	108 mm
Colour	Gris antracita
EAN	8421870027034
Manufacturer	SCHNEIDER
Material	PBT
No. of poles	3P
Weight (kg)	1,01 kg
Depth	71 mm
Protection	IP40
Nominal voltage (V)	230/400 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026