

Product sheet

Distribution Connector 3 Terminals 25 mm²

Brand: SCHNEIDER

Reference: IMPO 28949



Distribution connector terminal type for electrical installations in the ComPact range, compatible with INSE80 systems. Includes 3 terminals for 4 cables of 25 mm² section, with insulating separator. Designed for nominal currents up to 160 A, made from resistant materials and compliant with EU RoHS and REACH regulations.

[View product online](#)

Description

Distribution connector terminal type, designed for use in electrical systems of the ComPact (Compact INSE) range. Composed of a set of 3 terminals with 4 cables each, allowing secure and organized connections in industrial or distribution installations. Nominal current ranges from 0 to 160 A, suitable for medium-power applications.

Technical Features

- Product range: INS40...160 INSE80
- Range: ComPact
- Device short name: distribution connectors
- Product or component type: Terminal
- Accessory / separate part category: Connection accessory
- Range compatibility: Compact (Compact INSE) Compact (Compact INSE)
- Quantity per set: Set of 3
- [In] Nominal current: 0...160 A
- Number of units in package 1: 1
- Package 1 Height: 3.0 cm
- Package 1 Width: 10.0 cm
- Package 1 Length: 11.0 cm
- Package 1 Weight: 124.0 g

- Number of units in package 2: 30
- Package 2 Height: 30.0 cm
- Package 2 Width: 30.0 cm
- Package 2 Length: 40.0 cm
- Package 2 Weight: 4.148 kg
- Sustainable offering status: Green Premium Product
- REACH Regulation: Reference contains SVHC above threshold
- EU RoHS Directive: Compliant
- Free from toxic heavy metals: Yes
- Mercury-free: Yes
- China RoHS Regulation: Product outside the scope of China RoHS. Substance information declaration
- RoHS exemptions information: Yes
- WEEE: In the European Union market, the product must be disposed of according to a specific waste collection system and never end up in a regular trash container

Specifications

EAN	3303430289494
Manufacturer	SCHNEIDER
Range	Industrial
Intensity	160
Long	11,0 cm
Measures	11,0 cm
Weight (kg)	0,124 kg
Depth	3,0 cm
Cable cross-section (mm²)	25

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 October 2026