

Product sheet

Acti9 NG125L 2P 32 A D Curve Automatic Circuit Breaker

Brand: SCHNEIDER

Reference: IMPO 18843



Miniature automatic circuit breaker Acti9 NG125L, 2 poles, 32 A, D curve, with breaking capacity Icu of 50 kA at 380-415 V AC, 50/60 Hz, thermal-magnetic design, DIN 35 mm rail mounting, suitable for installations in small businesses and buildings, with position indicator and integrated lock.

[View product online](#)

Description

Miniature automatic circuit breaker from the Acti9 NG125 range, designed to protect electrical circuits in installations for small businesses and small buildings. Offers thermal and magnetic protection with D curve, suitable for loads with high starting currents.

Specifications

Frequency	50/60 Hz
Rated current (A)	32
Width	5,4 cm
Curve	D
EAN	3303430188438
Manufacturer	SCHNEIDER
Range	Industrial
No. of poles	2P
Weight (kg)	0,48
Depth	8,1 cm
Protection	IP20
Rated voltage	250
Nominal voltage (V)	220...240 V AC 50/60 Hz, 380...415 V AC 50/60 Hz, 440 V AC 50/60 Hz, 500 V AC 50/60 Hz, ≤ 250 V corriente continua
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 12 October 2026