

Product sheet

Industrial angled socket 125 A 3P+E IP67

Brand: SCHNEIDER

Reference: IMPO 81294



Recessed base with angled outlet, 125 A, 3P+E, 380...415 VAC, IP67. Designed for industrial installations in demanding environments. Connections via captive screws, cable section 16...70 mm². Housing material: engineering self-extinguishing polymer. Complies with standards EN 60309-1 and EN 60309-2. Fire resistance of 850 °C and IK08 protection rating.

[View product online](#)

Description

Recessed base with angled outlet from the PratiKa range, designed for industrial low-voltage applications. Ideal for secure and durable connections in fixed installations, especially in small businesses. Its robust structure and IP67 protection ensure reliable operation under adverse conditions.

Technical features

- Number of poles: 3P+E
- Network type: AC
- Rated current: 125 A
- Rated operating voltage: 380...415 V
- Supply frequency: 50/60 Hz
- Earth terminal position clockwise: 6 h
- Housing material: Engineering self-extinguishing polymer
- Contact material: Stainless steel pins and springs, nickel-plated brass sleeves
- Connections: Captive screws, fully loosened
- Cable section: 16...70 mm²
- Protection rating IP: IP67 according to IEC 60529
- IK protection rating: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-11
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C

- Operating ambient temperature: 35 °C (86400 s)
- Dimensions: 110 x 114 mm (base), height 114 mm, width 129 mm, depth 166 mm
- Weight: 1.205 kg
- Color: Grey (RAL 7035)
- Voltage color code: Red
- Standards: EN 60309-1, EN 60309-2
- Market segment: Small businesses
- Sustainable offering status: Green Premium product
- REACH Regulation: Contains SVHC above threshold
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS: Outside scope
- Mercury-free: Yes
- RoHS exemptions: Yes

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	129 mm
Colour	Grey
EAN	3303430812944
Manufacturer	SCHNEIDER
Range	Industrial
Long	110 mm
Material	Polímero
No. of poles	3P+E
Weight (kg)	1,205 kg
Depth	166 mm
Protection	IP67 - uso externo
Cable cross-section (mm²)	16
Nominal voltage (V)	380...415 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026