

## Product sheet

## Wall Mount Plug 32 A 3P IP67 90°

Brand: SCHNEIDER

Reference: IMPO 83870



Panel-mount plug for industrial installations, with 3 poles plus earth, rated for nominal current of 32 A, voltage of 380-415 V AC, frequency 50/60 Hz. Designed for demanding environments with IP67 protection rating and IK08 mechanical resistance. Made from self-extinguishing polymer, brass nickel-plated contacts, and screw-type non-loosening connections.

[View product online](#)

### Description

Wall-mount PratiKa-type plug, designed for industrial applications in demanding environments. Compatible with the PratiKa plug system, providing secure and durable connection in low-voltage installations with nominal current of 32 A and voltage of 380...415 V AC. Its 90° angled design facilitates connection in limited spaces.

### Technical Features

- Number of poles: 3P+E
- Power supply type: AC
- Rated current: 32 A
- Rated operating voltage: 380...415 V
- Supply frequency: 50/60 Hz
- Earth terminal position: 6 o'clock
- Socket and plug material: Engineering self-extinguishing polymer
- Contact material: Nickel-plated brass
- Connections: Non-loosening screws
- Cable cross-section: 2.5...10 mm<sup>2</sup>
- Protection rating: IP67 according to IEC 60529
- IK protection rating: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-1

- Operating ambient temperature: -25...40 °C
- Maximum operating altitude: 2000 m
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C
- Color: Grey (RAL 7035)
- Voltage color code: Red
- Product weight: 0.333 kg
- Dimensions: 91 x 100 mm (base), 159 mm (height), 90 mm (width), 112 mm (depth)
- Standards: EN 60309-1, EN 60309-2
- Market segment: Small businesses
- Sustainable offering status: Green Premium product
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope
- Contains SVHC above threshold
- Mercury-free

Specifications

|                           |                    |
|---------------------------|--------------------|
| Frequency                 | 50/60 Hz           |
| Rated current (A)         | 32                 |
| Width                     | 90 mm              |
| Colour                    | Grey               |
| EAN                       | 3303430838708      |
| Manufacturer              | SCHNEIDER          |
| Range                     | Industrial         |
| Long                      | 159 mm             |
| Material                  | Polímero           |
| No. of poles              | 3P+E               |
| Weight (kg)               | 0,333              |
| Depth                     | 112 mm             |
| Protection                | IP67 - uso externo |
| Cable cross-section (mm²) | 10 mm²             |
| Nominal voltage (V)       | 380...415 V        |
| Current type              | AC                 |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 October 2026