

Product sheet

Basic digital output kit 4 channels 24 V DC

Brand: SCHNEIDER

Reference: IMPO STBDDO3415K



Basic digital output kit for Modicon STB systems, with 4 solid state outputs, 24 V DC operating voltage, positive logic, 560 μ s off-a-on response and 870 μ s on-a-off. Compatible with STBXBA1000 base and STBPDT3100/3105 power distribution module.

[View product online](#)

Description

Basic digital output kit for industrial automation systems, compatible with the Modicon STB range distributed I/O solution. Designed to control up to 4 digital outputs in industrial environments, with connection via screw connector and spring clamp. It works with 24 V DC voltage and positive logic, offering quick responses with 560 μ s (off-a-on) and 870 μ s (on-a-off) times.

Technical characteristics

- Number of digital outputs: 4
- Digital output type: Solid state
- Output voltage: 24 V DC
- Logic of discrete output: Positive
- Output voltage: 19,2...30 V DC
- Maximum absolute voltage: 56 V for 1.3 ms
- Response time: 560 μ s (off-a-on), 870 μ s (on-a-off)
- Cold exchange: Yes
- Delayed hot exchange: Not for basic NIM
- Integrated protection: PDM fuse (5A), reverse polarity, short circuit, thermal overload
- Inter-channel isolation and logic bus: 1500 V for 1 minute
- Overvoltage current: 2.5 A for 0.5 ms
- Maximum load capacity: 50 μ F
- Current consumption: 70 mA in 5 V DC for logic bus
- Power supply: Power distribution module

- Operating ambient temperature: 0...60 °C
- Storage ambient temperature: -40...85 °C
- Relative humidity: 95 % at 60 °C without condensation
- Vibration resistance: 3 gn in 58...150 Hz (DIN 35 x 7.5 mm), 5 gn in 58...150 Hz (DIN 35 x 15 mm), ±0.35 mm in 10...58 Hz
- Shock resistance: 30 gn for 11 ms
- Degree of protection: IP20 according to IEC 61131-2 class 1
- Degree of contamination: 2 according to IK07
- Maximum operating altitude: ≤ 2000 m
- Status LED: 1 green LED (RDY), 1 green LED per channel (OUT1 to OUT4)
- Compatibility: I/O STBXBA1000 base, power distribution module STBPDT3100/3105
- Standards: IEC 61131-2
- Certifications: CE, CSA NF UL
- Weight of product: 0.11 kg
- Height: 13.9 mm
- Depth: 70 mm
- Width: 128.3 mm

Specifications

High	13,9 mm
Width	128,3 mm
EAN	3595863989281
Manufacturer	SCHNEIDER
# Elements	4
Weight (kg)	0,11 kg
Depth	70 mm
Protection	IP20
Nominal voltage (V)	24

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team