

Product sheet

PratiKa Wall Socket 125 A 3P+N+E IP67

Brand: SCHNEIDER

Reference: IMPO 81595



Industrial wall socket 3P+N+E, with a nominal current of 125 A and operating voltage of 380...415 V AC, designed for recessed wall mounting. Compatible with standards EN 60309-1 and EN 60309-2, features IP67 protection rating and IK08 impact resistance.

[View product online](#)

Description

PratiKa industrial wall socket with 3P+N+E connection, designed for low-voltage installations in industrial environments and small commercial settings. Compatible with the PratiKa system, it provides a secure and robust connection for loads up to 125 A and voltages of 380...415 V AC, operating at 50/60 Hz. Its angled design and recessed wall mounting facilitate integration into limited spaces.

Technical Features

- Number of poles: 3P+N+E
- Nominal current: 125 A
- Nominal operating voltage: 380...415 V AC
- Supply frequency: 50/60 Hz
- Earth terminal position: 6 o'clock
- Socket and plug material: Engineering self-extinguishing polymer
- Contact material: Nickel-plated brass pins
- Connections: Non-loosening screws
- Cable cross-section: 16...70 mm²
- Cable entry: Cable gland
- Thread type: Pg 48
- Protection rating IP: IP67
- Impact protection rating IK: IK08
- Fire resistance: 850 °C
- Maximum operating altitude: 2000 m

- Operating ambient temperature: -25...40 °C
- Weight: 1.864 kg
- Dimensions: 114 x 224 x 354 mm (width x depth x height)
- Color: Grey (RAL 7035)
- Voltage code: Red
- Standards: EN 60309-1, EN 60309-2

Designed for demanding industrial environments, its robust construction and IP67 protection ensure safe operation under adverse conditions. Ideal for applications in small commercial settings and environments exposed to dust and moisture.

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Colour	Grey
EAN	3303430815952
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
No. of poles	3P+N+E
Weight (kg)	1,864 kg
Protection	IP67 - uso externo
Nominal voltage (V)	380...415 V AC
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026