

Product sheet

Surface Mount 63 A 2P+E IP67 Grey

Brand: SCHNEIDER

Reference: IMPO 81678



Surface mount 63 A 2-pole T 200-250 V IP67, panel-mounted, with captive screw terminals, compatible with industrial standard, impact resistant IK08 and IP67 protected, designed for demanding industrial environments, with stainless steel and nickel-plated brass contacts, supports frequencies 50/60 Hz and cable cross-section 6–25 mm².

[View product online](#)

Description

Surface mount 63 A 2-pole T 200-250 V IP67, designed for industrial applications with panel mounting. Compatible with international standards, provides a secure and durable connection in demanding environments.

Technical Features

- Number of poles: 2P+E
- Power supply type: AC
- Output standard: Industrial
- Rated operating voltage: 200...250 V
- Rated current: 63 A
- Supply frequency: 50/60 Hz
- Earth terminal position clockwise: 6 o'clock
- Housing material: Engineering self-extinguishing polymer
- Contact material: Stainless steel pins and springs, nickel-plated brass sleeves
- Connections: Captive screws, fully loosened
- Cable cross-section: 6...25 mm²
- Protection degree IP: IP67 according to IEC 60529
- Impact protection degree IK: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-11

- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C
- Operating ambient temperature: 35 °C (86400 s)
- Color: Grey (RAL 7035)
- Voltage color code: Blue
- Standards: EN 60309-1, EN 60309-2
- Product weight: 0.424 kg
- Base dimensions: 325 x 175 x 120 mm
- Height: 107 mm
- Width: 108 mm
- Depth: 113 mm
- Compatibility code: PratiKa Socket
- Sustainable offering status: Green Premium Product
- REACH Regulation: Contains SVHC above threshold
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope
- RoHS Exemptions: Yes
- Mercury-free: Yes

Specifications

Frequency	50/60 Hz
Rated current (A)	63
Width	108 mm
EAN	3303430816782
Manufacturer	SCHNEIDER
Range	Industrial
Long	107 mm
Material	Polímero
No. of poles	2P+E
Weight (kg)	0,424 kg
Depth	113 mm
Protection	IP67 - uso externo
Rated voltage	250
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 9 October 2026