

Product sheet

2-position selector head black textured knob

Brand: SCHNEIDER

Reference: IMPO ZB4BD29



Standard 2-position selector head with rough black knob, 22 mm front mount, made of silver chromed metal. Designed for demanding industrial applications, it offers high pressure wash resistance (IP69K), 1,000,000-cycle mechanical durability and shock protection (IK06).

[View product online](#)

Description

Standard 2-position selector head with black rough knob, designed for 22 mm front mounting. Made of silver chromed metal, it is designed for demanding industrial applications, offering high mechanical resistance and protection against aggressive environments.

Technical characteristics

- Mounting diameter: 22 mm
- Signalling head shape: Circular
- Type of operator: Fixed
- Operator profile: Black Rugged Perilla
- Operator position information: 2 90° positions
- Global width cad: 29 mm
- Overall height cad: 29 mm
- Global depth cad: 44 mm
- Product weight: 0.043 kg
- High pressure wash resistance: 7000000 Pa at 55 °C, distance: 0.1 m
- Mechanical durability: 1000000 cycles
- Degree of IP protection: JIS C8201-1 according to Enable / Deactivate Ig IP69K
- Degree of NEMA protection: NEMA 13 NEMA 4X
- Level of protection IK: IK06 according to IEC 50102
- Vibration resistance: 5 gn (f = 2...500 Hz) according to IEC 60068-2-6
- Shock resistance: 30 gn (length 18 ms) and 50 gn (length 11 ms) according to IEC 60068-2-27

- Storage ambient temperature: -40...70 °C
- Operating ambient temperature: -40...70 °C
- Electrical shock protection class: Class I according to IEC 60536
- Electrical composition code: C3 for C4 for C5 for C6 for C7 for C8 for C11 for C15 for <1 contacts use Single blocks in front mounting
- Standards: EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-5-4 EN/IEC 60947-1 CSA C22.2 No 14 JIS C8201-5-1 JIS C8201-1
- Product certifications: LROS (Lloyds Register of Shipping) CSA BV GL Registered by UL DNV
- Protection treatment: TC
- Sustainable supply status: Product Green Premium
- According to REACH without SVCC: Yes
- EU RoHS Directive: Proactive compliance (out-of-scope product of RoHS EU)
- Without toxic heavy metals: Yes
- No mercury: Yes
- Information on RoHS exemptions: Yes
- RoHS China Regulations: X

Specifications

Colour	Cromado
Diameter	22 mm
EAN	3389110889123
Manufacturer	SCHNEIDER
Range	Industrial
Long	44 mm
Weight (kg)	0,043 kg

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 9 October 2026