

Product sheet

Current Transformer 400 A, 4-Pole, Class 0.5

Brand: SCHNEIDER

Reference: IMPO LV432654



4-pole current transformer, 400 A, ratio 400/5 A, accuracy class 0.5, rated voltage 530 V, frequency 50/60 Hz, connection via 2.5 mm² cable connector, protection rating IP40 and IK04, compatible with ComPact NSX400/630, INSE and NB ranges, designed for control applications in AC systems.

[View product online](#)

Description

Current transformer block with voltage measurement output for control systems in electrical installations, compatible with new generation ComPact NSX400 and NSX630, as well as Compact INSE and Compact NB. Designed for integration into AC network current protection and monitoring systems.

Technical Features

- Number of poles: 4P
- Rated current [In]: 400 A
- Transformation ratio: 400/5 A
- Power consumption: 2 VA
- Accuracy class: Class 0.5
- Rated operating voltage [Ue]: 530 V
- Network type: AC
- Supply frequency: 50/60 Hz
- Auxiliary connection terminal: 2.5 mm² cable connector
- Electric shock protection class: Class II
- Protection rating IP: IP40 according to IEC 60529
- Impact protection rating IK: IK04 according to IEC 62262
- EU RoHS Directive: Compliant
- Green Premium product
- Contains SVHC above threshold (REACH)

- RoHS exemptions: Yes
- Product outside the scope of China RoHS

Specifications

Frequency	50/60 Hz
Rated current (A)	400
EAN	3606480020827
Manufacturer	SCHNEIDER
No. of poles	4P
Protection	IP40
Cable cross-section (mm²)	2,5 mm²
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026