

Product sheet

Acti9 NG125N 3P 16 A C Curve Automatic Switch

Brand: SCHNEIDER

Reference: IMPO 18633



Miniature automatic switch Acti9 NG125N, 3 poles, 16 A, C curve, with breaking capacity I_{cu} of 25 kA at 380–415 V AC, designed for use in small commercial applications.

[View product online](#)

Description

Miniature circuit breaker from the Acti9 NG125N range, designed to protect electrical circuits in industrial and commercial installations.

Technical Features

- Number of poles: 3P
- Number of protected poles: 3
- Rated current [I_n]: 16 A at 40 °C
- Network type: AC Direct current
- Tripping curve: C
- Breaking capacity I_{cu} : 25 kA at 380–415 V AC 50/60 Hz
- Service breaking capacity [I_{cs}]: 15 kA (75 % of I_{cu}) at 440 V AC 50/60 Hz
- Rated operating voltage [U_e]: 220–240 V, 380–415 V, 440 V, 500 V AC 50/60 Hz
- Rated insulation voltage [U_i]: 690 V AC 50/60 Hz
- Surge voltage withstand [U_{imp}]: 8 kV
- Supply frequency: 50/60 Hz
- Contact position indicator: Yes
- Local indicators: Trip indicator, on/off indication
- Mounting support: Symmetrical 35 mm DIN rail
- Height: 103 mm
- Width: 81 mm
- Depth: 81 mm

- Weight: 0.72 kg
- Mechanical durability: 20 000 cycles
- Electrical durability: 10 000 cycles
- Lockable: With integrated lock
- Connections: Tunnel-type terminals (1.5–50 mm² rigid, 1–35 mm² flexible)
- Stripping length: 20 mm
- Tightening torque: 3.5 N·m
- Protection degree IP: IP20
- Impact protection degree IK: IK05
- Contamination degree: 3
- Overvoltage category: IV
- Tropicalization: 2
- Operating ambient temperature: -30 °C to +70 °C
- Storage ambient temperature: -40 °C to +70 °C
- Standards: Icu
- Compliant with EU RoHS, REACH without SVHC, mercury-free, free of toxic heavy metals

Specifications

Frequency	50/60 Hz
Rated current (A)	16
Width	81 mm
Curve	C
EAN	3303430186335
Manufacturer	SCHNEIDER
Range	Industrial
Long	103 mm
No. of poles	3P
Weight (kg)	0,72 kg
Depth	81 mm
Protection	IP20
Cable cross-section (mm ²)	35 mm ²
Nominal voltage (V)	220–240 V, 380–415 V, 440 V, 500 V AC 50/60 Hz

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026