

Product sheet

Acti9 NG125N 3P 20 A C Curve Automatic Switch

Brand: SCHNEIDER

Reference: IMPO 18634



Miniature automatic switch Acti9 NG125N, 3 poles, 20 A, C curve, with breaking capacity I_{cu} of 25 kA at 380–415 V AC, thermal-magnetic design, DIN 35 mm rail mounting, suitable for small commercial installations with IP20 protection and pollution degree 3.

[View product online](#)

Description

Miniature circuit breaker, model Acti9 NG125N, designed for electrical circuit protection in industrial and commercial installations.

Technical Features

- Number of poles: 3P
- Number of protected poles: 3
- Rated current [I_n]: 20 A at 40 °C
- Network type: AC Direct current
- Tripping curve: C
- Breaking capacity I_{cu} : 20 kA (500 V AC), 25 kA (380–415 V AC), 50 kA (220–240 V AC)
- Service breaking capacity [I_{cs}]: 37.5 kA (220–240 V AC), 18.75 kA (380–415 V AC), 15 kA (440 V AC), 7.5 kA (500 V AC), 20 kA (≤ 375 V DC)
- Rated operating voltage [U_e]: 220–240 V AC, 380–415 V AC, 440 V AC, 500 V AC
- Rated insulation voltage [U_i]: 690 V AC
- Surge voltage withstand [U_{imp}]: 8 kV
- Supply frequency: 50/60 Hz
- Contact position indicator: Yes
- Local indicators: Trip indicator, on/off indication
- Mounting: Adjustable clip, symmetrical DIN 35 mm rail mounting support
- Connections: Tunnel-type terminals (1.5–50 mm² rigid, 1–35 mm² flexible)
- Stripping length: 20 mm

- Tightening torque: 3.5 N·m
- Lockable: With integrated lock
- Mechanical durability: 20 000 cycles
- Electrical durability: 10 000 cycles
- Protection degree IP: IP20
- Impact protection degree IK: IK05
- Pollution degree: 3
- Overvoltage category: IV
- Tropicalization: 2
- Operating ambient temperature: -30 °C to 70 °C
- Storage ambient temperature: -40 °C to 70 °C
- Weight: 0.72 kg
- Standards: Icu
- Compliant with EU RoHS, REACH without SVHC, mercury-free, free from toxic heavy metals

Specifications

Frequency	50/60 Hz
Rated current (A)	20
Curve	C
EAN	3303430186342
Manufacturer	SCHNEIDER
Range	Industrial
No. of poles	3P
Weight (kg)	0,72 kg
Protection	IP20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 14 October 2026