

Product sheet

Spacial SF 500 mm bar support

Brand: SCHNEIDER

Reference: IMPO NSYAS500



SF Space Bar holder of 500 mm nominal height, designed for vertical mounting at the bottom of the cabinet. Made of plastic insulating support and steel metal support. Compatible with the Spacial SF, Linergy LGYE, Linergy BS, Spacial SFP and Prisma PH ranges. Height: 66 mm, depth: 39 mm, fixing centers: 450 mm.

[View product online](#)

Description

500 mm Space SF configuration bracket designed for installation at the bottom of the cabinet, providing a stable vertical structure for attachment of elements in distribution systems. Compatible with the Spacial SF, Linergy LGYE, Linergy BS, Spacial SFP and Prisma PH ranges, especially in applications for Prism Multiuso.

Technical characteristics

- Range: Spacial
- Product type: Bar support (*)
- Function: Application for Multipurpose Prism
- Mounting location: Lower part
- Distribution position: Vertical
- Range compatibility: Spacial (Spatial SF), Linergy (Linerger LGYE), Linergy (Linerger BS), Spacial (Spatial SFP), Prisma (Prisma PH)
- Connection of cell devices: Linergy LGYE side muddy, Linergy BS side muddy
- Composition of the device: fixation elements, 1 insulating bar support, 1 metal support
- Amount per game: Game of 1
- Material: Support bar (plastic), metal support (steel)
- Fixing mode: By fixing element - lower cabinet frame
- Height: 66 mm
- Width: Fixing centres 450 mm, nominal 500 mm
- Depth: 39 mm

- Package weight 1: 1,148 kg
- Package weight 2: 128.0 kg
- Number of units in package 1: 1
- Number of units in package 2: 100
- Sustainable supply status: Product Green Premium
- REACh Regulation: Contains SVHC over the threshold
- EU RoHS Directive: Proactive (out-of-scope) compliance
- RoHS China Regulations: Outside the scope
- Information on RoHS exemptions: Yes
- No mercury: Yes

Specifications

High	66 mm
Width	450 mm
EAN	3606480062858
Manufacturer	SCHNEIDER
Material	Steel
Measures	66 mm x 450 mm x 39 mm
# Elements	1 elemento
Weight (kg)	1,148 kg
Depth	39 mm

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026