

Product sheet

**S&P Window helical extractor
230V 543 m³/h**

Brand: S&P

Reference: SYP 5201421400



Helical extractor for glass or wall installation, with ABS housing and positive pressure shutter. 230V-50Hz motor, class B and IPX4 protection. Moves 543 m³/h with safety grilles on intake and discharge, compatible with electronic control.

[View product online](#)**Description**

Helical extractor HCM-225-N designed for installation in glass or wall. This ventilation unit is equipped with an ABS plastic housing and an integrated positive pressure shutter, ensuring efficient and safe airflow in enclosed spaces.

Technical features

- Airflow volume: 543 m³/h
- Connection voltage: 230 V
- Power consumption: 0.03 W
- Protection rating: IPX4
- Maximum air temperature: 45 °C
- Electrical connection: Connection flange
- Compatible with electronic control: Yes
- Operation: Electrical power supply
- Safety grilles on intake and discharge

Compatibility with electronic control allows flexible management of airflow. The design includes safety grilles that protect both the air inlet and outlet, improving the operational safety of the device.

Specifications

EAN	8413893128881
Manufacturer	S&P
Material	ABS

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 27 October 2026